



## Einzelwertkarte




## statistische Kenndaten


Cm: 2.90  
 Cmk: 2.62  
 Tol. unten: 3.60  
 Tol. oben: 4.40  
 Sollwert: 4.00  
 Max: 4.15  
 Min: 3.94  
 x-quer: 4.04  
 s: 0.05  
 x + 3s: 4.18  
 x - 3s: 3.90  
 Anzahl Messwerte: 100  
 Winkel: 30  
 Verschraubungsklasse: 2 - Toleranz +/- 10%  
 rechtsdrehend  
 mittlere Geschwindigkeit: 891



## Häufigkeitsbild



## Wahrscheinlichkeitsnetz



Einzelwerte:	1. 4.05	6. 4.02	11. 4.08	16. 4.06	21. 3.99	26. 4.02	31. 4.06	36. 4.11	41. 3.94	46. 3.99	51. 4.10	56. 3.98	61. 4.02	66. 4.00	71. 4.15	76. 4.12	81. 4.00	86. 4.03	91. 4.09	96. 4.11
	2. 4.07	7. 4.07	12. 4.03	17. 4.06	22. 4.07	27. 4.03	32. 3.97	37. 4.01	42. 3.95	47. 4.10	52. 4.04	57. 3.95	62. 4.02	67. 4.01	72. 4.05	77. 4.00	82. 4.05	87. 4.09	92. 4.04	97. 4.04
	3. 4.01	8. 4.07	13. 4.09	18. 4.11	23. 4.01	28. 3.98	33. 3.96	38. 4.02	43. 4.02	48. 4.07	53. 3.98	58. 3.98	63. 4.01	68. 4.03	73. 4.03	78. 4.02	83. 4.00	88. 4.08	93. 4.05	98. 4.04
	4. 4.07	9. 3.98	14. 4.05	19. 4.09	24. 4.06	29. 3.99	34. 4.07	39. 3.98	44. 4.00	49. 4.11	54. 3.97	59. 4.02	64. 4.06	69. 4.01	74. 4.07	79. 4.11	84. 4.07	89. 4.04	94. 4.04	99. 4.12
	5. 4.03	10. 4.04	15. 4.09	20. 4.00	25. 4.07	30. 4.00	35. 4.02	40. 4.00	45. 3.97	50. 4.08	55. 3.96	60. 4.00	65. 4.05	70. 4.08	75. 4.04	80. 4.05	85. 4.13	90. 4.12	95. 4.08	100. 4.06

A 185 000 005.1 - 9,6 V - 1.00-4.00 Nm - 1.Muster - 0 602 490 437 - 9,6 - Bosch - Schrauber (allg.)

MFU vom 08.06.2001

Einheit: MD [Nm]  
Normalverteilung

Anzahl Messwerte: 100  
Toleranz

Mittelwert (x-quer): 4.04  
Standardabweichung: 0.05  
Sollwert

Cm: 2.90  
Cmk: 2.62  
Mittelwert (x-quer):

6s (x ± 3 s)

i. O.