



Firma



Sanwald

11.05.2006 11:22:07

MtB/EMG3

249

Seite 1/1



| | | | | | | | | | | |
|--------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|-----------|
| Einzelwerte: | 01. 3.57 | 02. 3.51 | 03. 3.57 | 04. 3.58 | 05. 3.59 | 06. 3.58 | 07. 3.58 | 08. 3.57 | 09. 3.58 | 10. 3.57 |
| | 11. 3.66 | 12. 3.59 | 13. 3.65 | 14. 3.65 | 15. 3.57 | 16. 3.57 | 17. 3.57 | 18. 3.55 | 19. 3.60 | 20. 3.61 |
| | 21. 3.56 | 22. 3.60 | 23. 3.63 | 24. 3.57 | 25. 3.51 | 26. 3.56 | 27. 3.52 | 28. 3.60 | 29. 3.64 | 30. 3.58 |
| | 31. 3.61 | 32. 3.60 | 33. 3.56 | 34. 3.58 | 35. 3.56 | 36. 3.55 | 37. 3.56 | 38. 3.51 | 39. 3.55 | 40. 3.59 |
| | 41. 3.57 | 42. 3.61 | 43. 3.56 | 44. 3.55 | 45. 3.55 | 46. 3.53 | 47. 3.56 | 48. 3.55 | 49. 3.53 | 50. 3.57 |
| | 51. 3.52 | 52. 3.57 | 53. 3.57 | 54. 3.59 | 55. 3.58 | 56. 3.52 | 57. 3.54 | 58. 3.53 | 59. 3.54 | 60. 3.58 |
| | 61. 3.56 | 62. 3.57 | 63. 3.54 | 64. 3.59 | 65. 3.56 | 66. 3.62 | 67. 3.55 | 68. 3.56 | 69. 3.60 | 70. 3.55 |
| | 71. 3.57 | 72. 3.57 | 73. 3.58 | 74. 3.57 | 75. 3.52 | 76. 3.44 | 77. 3.50 | 78. 3.55 | 79. 3.53 | 80. 3.55 |
| | 81. 3.45 | 82. 3.57 | 83. 3.54 | 84. 3.55 | 85. 3.51 | 86. 3.45 | 87. 3.54 | 88. 3.53 | 89. 3.55 | 90. 3.53 |
| | 91. 3.54 | 92. 3.57 | 93. 3.54 | 94. 3.58 | 95. 3.55 | 96. 3.54 | 97. 3.52 | 98. 3.51 | 99. 3.54 | 100. 3.44 |

- E 682 000 106 - 0.50-3.50 Nm - 0.00 -0 602 495 200 -Bosch -Schrauber (allg.)

MFU vom 11.05.2006 auf BLM3850 (3860SK.055 -) Zelle/Kanal 2

Einheit: MD [Nm]Anzahl Messwerte: 1Mittelwert (x-quer): Standardabweichung: 0.04 Cm: 2.97

Cmk: 2.46 i. O.

Normalverteilung

Toleranz

Sollwert

Mittelwert (x-quer):

6s (x ± 3 s)